
EA13 electric towel rack user manual



Safety warning

To avoid injury to infants, install the lowest heating rack at least 24 in from the floor. If the power cord is damaged, it must be repaired by a professional electrician in order to avoid danger.

Packing list

Wall bracket ❶ x4



Expansion screw assembly ❷ x4



Install auxiliary sticker ❸ x1



Specification (Certificate) ❹ x1



connecting rod ❺ x1



connecting rod ❻ x3



screw ❼ x4 M4*70mm



screw ❽ x6 M5*7mm



screwdriver ❾ x1



plug ❿ x1




hanger ⓫ x2



screw ⓬ x4 M4*12mm



Operator panel description



Function Introduction


When turned off, the brightness of LED1 keeps changing, creating a breathing effect, while other LEDs or digital tubes turn off. Long press or short press "Switch" to turn on the device. After turning on, the digital display shows the set test or timer time, and LED1, LED2, and LED3 light up.
Long press or short press "Switch" in the power on state to turn off t he device. The brightness of LED1 keeps changing, showing a breathing effect, while other LEDs or digital tubes turn off.

In the power on state, short press "Temperature" and the digital tube will flash. At this time, the temperature can be set. Press "Temperature" again and the set temperature will cycle from P1->P2->P3->P1. After no button operation, the digital tube will flash for about 5 seconds, and the setting will take effect.


In the power on state, press "Timing" and the digital display will show the timer time. If the timer time is zero, it will display "- h". Press "Timing" again and the digital display will show the timer temperature for 1 hour ->2 hours ->3 hours ->4 hours ->5 hours ->6 hours -> 7 hours ->8 hours–24 hours ->- - h cycle (- h refers to no timer and will automatically exit the timer state). After flashing for about 5 seconds, it will exit the set state and take effect, and the digital display will show the timed time.

At the end of the timer, the system enters a shutdown state, and the brightness of LED1 keeps changing, showing a breathing effect, while other displays turn off.
"on" Continuous illumination after startup.


Installation instructions




The first step is to mark the installation with auxiliary stickers and drill holes with M6 drill bit.




Lock 7 onto the product through 5 or 6



Lock 1 onto the wall with 2, insert 5 or 6 into 1, and lock 8 onto 1 with 9,Fixed 5 or 6





Remove the protective cover, The plug can be inserted into any connector




insert 5 or 6 into 1, and lock 8 onto 1 with 9,Fixed 5 or 6

Hidden line installation






insert 6 into 1, and lock 8 onto 1 with 9,Fixed 6




Lock 11 onto the main body with 12 locks

Sizing specification


EA13-450



EA13-800



EA13-1000



Environmental statement

Storage environment: Temperature :-104~185°F; Relative humidity 20%~95%.

Use environment:Temperature: product use environment temperature≤185°F;

Relative humidity : 40%~85%.

Test environment: Test environment specified in relevant test standards.

Basic parameter

Product name	Electric towel rack	Colour	Multiple color options
Model	EA13	Input voltage	AC 110 V
Weight	See the manual	Drying range	P1 / P2 / P3 104°F /122°F /140°F
Size	See the attached diagram		
Power	EA13-450 / 800 / 1000 95w 135w 165w	Waterproofing grade	IPX4

Please keep this instruction manual and contact us if you need any technical support or after-sale service.We will respond ASAP.